



TECHNICAL DATA

- ENCLOSURE :-
EX-d AS PER IS/ICE 60079-1:2007
- PROTECTION :-
IP-66 AS PER IS/IEC 60529:2001
- AREA CLASSIFICATION :-
ZONE -1 & 2
- GAS GROUP :-
IIA, IIB & IIC
- MATERIAL OF CONSTRUCTION :-
DIE CAST AL. ALLOY
- TRANSPARENT PART :-
HEAT RESISTANT & TOUGHENED CLEAR TUBULAR GLASS
AS PER IS:2206 (PART-II)
- GASKET :-
ENDLESS MOULDED NEOPRENE
- HARDWARE :-
STEEL ZINC PLATED/STAINLESS STEEL
- FINISH :-
LIGHT GREY POWDER COATED.
- EARTHING :-
1 NO. INSIDE & 2 NOS. OUTSIDE
- CABLE ENTRY :-
3/4"ET - 02NOS.
- OPTIONAL ACCESSORIES AT EXTRA COST :-
1) EXTERNAL REFLECTOR
2) WIRE GUARD
3) MOUNTING BRACKET AS PER CLIENT REQUIREMENT
4) HINGE ARRANGEMENT
5) PAINT SHADE AS PER CLIENT REQUIREMENT
6) CABLE GLAND & STOPPER
7) TUBE LAMP
8) ELECTRONIC BALLAST

TYPE NO.	ELECTRICAL RATING	TEMP. CLASS
KTL-A	1X36/40W, 240V FTL	T6
	1X28W, 240V T5 FTL	
	2X28W, 240V T5 FTL	
	2X36/40W, 240V FTL	
	3X36/40W, 240V FTL	
	4X36/40W, 240V FTL	
	4X54W, 240V T5 FTL	

ISSUE	DATE	BY	MODIFICATION

CLIENT	DRAWN	MJP
CONSULTANT	CH'D	MJP
P.O.No.	APP'D	MJP
KAYSONS TECHNO EQUIPMENTS PVT LTD		
1802/7, G.I.D.C. ESTATE, V.U.NAGAR 388121. (GUJARAT)		

DESCRIPTION:- FLAMEPROOF & WEATHERPROOF FLUORESCENT TUBE LIGHT FITTING		
SHT.NO. 1 OF 1	REV. 0	DRG.NO.:- A16