



TECHNICAL DATA

ENCLOSURE :-
EX-d AS PER IS/IEC 60079-1:2007

PROTECTION :-
IP-66 AS PER IS 12063-1987 (IS/IEC 60529:2001)

AREA CLASSIFICATION :-
ZONE -1 & 2

TEMPERATURE CLASS :-
T6

GAS GROUPS :-
IIA, IIB & IIC

MATERIAL OF CONSTRUCTION :-
DIE CAST AL. ALLOY LM-6

HARDWARE :-
STEEL ZINC PLATED/STAINLESS STEEL

FINISH :-
LIGHT GREY | YELLOW
FOR IIA & IIB | FOR IIC

EARTHING :-
1 NO. INSIDE & 2 NOS. OUTSIDE

CABLE ENTRY :-
3/4"ET - 2NOS.

08.	BELL	1	M.S. CHROME PLATED
07.	WIRE BUSH	1	GLASSFEEL NYLONE
06.	TERMINAL	A.R.	CLIPON TYPE RAIL MOUNTED
05.	GASKET (ENDLESS, MOULDED)	2	NEOPRENE
04.	OPERATING COIL WITH HAMMER	1	-
03.	TERMINAL BOX COVER	1	DIE CAST AL. ALLOY
02.	MAIN BODY COVER	1	DIE CAST AL. ALLOY
01.	BODY	1	CAST AL. ALLOY
NO.	DESCRIPTION	QTY	MAT./RATING

ISSUE	DATE	BY	MODIFICATION

CLIENT :-		DRAWN	MGP	1.9.16	DESCRIPTION:- FLAMEPROOF WEATHERPROOF ELECTRIC GONG BELL		
CONSULTANT :-		APP'D	HPB	1.9.16			
P.O.NO. :-		CH'D	NPB	1.9.16			
		1802/7, G.I.D.C. ESTATE, V.U.NAGAR 388121. (GUJARAT)			SHT.NO. 1 OF 1	REV. 0	DRG.NO.:- C01