



TECHNICAL DATA

ENCLOSURE :-
EX-d AS PER IS/IEC 60079-1:2007

PROTECTION :-
IP-66 AS PER IS 12063-1987 (IS/IEC 60529:2001)

AREA CLASSIFICATION :-
ZONE -1 & 2

TEMPERATURE CLASS :-
T6

GAS GROUPS :-
IIA & IIB

MATERIAL OF CONSTRUCTION :-
DIE CAST AL. ALLOY LM-6

HARDWARE :-
STEEL ZINC PLATED/STAINLESS STEEL

FINISH :-
LIGHT GREY POWDER COATED

EARTHING :-
1 NO. INSIDE & 2 NOS. OUTSIDE

CABLE ENTRY :-
3/4"ET - 03NOS.

09.	GASKET (ENDLESS, MOULDED)	2	NEOPRENE
08.	TERMINAL	A.R.	CLIPON TYPE RAIL MOUNTED
07.	CONTACTOR & O/L RELAY	1SET.	A.R.
06.	STOP PUSH BUTTON ACTUATOR	1	P.P
05.	START PUSH BUTTON ACTUATOR	1	P.P
04.	WIRE BUSH	1	GLASSFEEL NYLONE
03.	TERMINAL BOX COVER	1	DIE CAST AL. ALLOY
02.	BODY COVER	1	DIE CAST AL. ALLOY
01.	BODY	1	DIE CAST AL. ALLOY
NO.	DESCRIPTION	QTY	MAT./RATING

ISSUE	DATE	BY	MODIFICATION	CLIENT	DRAWN	CH'D	APP'D	DESCRIPTION:-
				CONSULTANT	MBO	MBO	MBO	FLAMEPROOF WEATHERPROOF
				P.O.No.				DOL STARTER UPTO 15 HP
								SHT.NO.
								REV.
								DRG.NO.:-
								1 OF 1
								0
								G01



KAYSONS
TECHNO EQUIPMENTS PVT LTD

1802/7, G.I.D.C. ESTATE,
V.U.NAGAR 388121. (GUJARAT)

01.09.16