



TECHNICAL DATA

ENCLOSURE :-  
EX-d AS PER IS/IEC 60079-1:2007

PROTECTION :-  
IP-66 AS PER IS 12063-1987 (IS/IEC 60529:2001)

AREA CLASSIFICATION :-  
ZONE -1 & 2

TEMPERATURE CLASS :-  
T6

GAS GROUPS :-  
IIA & IIB

MATERIAL OF CONSTRUCTION :-  
DIE CAST AL. ALLOY LM-6

HARDWARE :-  
STEEL ZINC PLATED/STAINLESS STEEL

FINISH :-  
LIGHT GREY POWDER COATED

EARTHING :-  
1 NO. INSIDE & 2 NOS. OUTSIDE

CABLE ENTRY :-  
3/4"ET - 03NOS.

10.	SWITCH	1	A.R.
09.	GASKET (ENDLESS, MOULDED)	2	NEOPRENE
08.	TERMINAL	A.R.	CLIPON TYPE RAIL MOUNTED
07.	CONTACTOR & O/L RELAY	1SET.	A.R.
06.	STOP PUSH BUTTON ACTUATOR	1	P.P
05.	START PUSH BUTTON ACTUATOR	1	P.P
04.	WIRE BUSH	1	GLASSFEEL NYLONE
03.	TERMINAL BOX COVER	1	DIE CAST AL. ALLOY
02.	BODY COVER	1	DIE CAST AL. ALLOY
01.	BODY	1	DIE CAST AL. ALLOY
NO.	DESCRIPTION	QTY	MAT./RATING

CLIENT		DRAWN	MLP	DESCRIPTION:- FLAMEPROOF WEATHERPROOF DOL STARTER UPTO 15 HP
CONSULTANT		CH'D	MLP	
P.O.No.		APP'D	MLP	
		1802/7, G.I.D.C. ESTATE, V.U.NAGAR 388121. (GUJARAT)		SHT.NO. 1 OF 1
MODIFICATION				REV. 0
ISSUE	DATE	BY		DRG.NO.:- G02