



TECHNICAL DATA

ENCLOSURE :-
EX-d AS PER IS/IEC 60079-1:2007

PROTECTION :-
IP-66 AS PER IS 12063-1987 (IS/IEC 60529:2001)

AREA CLASSIFICATION :-
ZONE -1 & 2

TEMPERATURE CLASS :-
T6

GAS GROUPS :-
IIA & IIB

MATERIAL OF CONSTRUCTION :-
DIE CAST AL. ALLOY LM-6

HARDWARE :-
STEEL ZINC PLATED/STAINLESS STEEL

FINISH :-
LIGHT GREY POWDER COATED

EARTHING :-
1 NO. INSIDE & 2 NOS. OUTSIDE

CABLE ENTRY :-
3/4"ET - 03NOS.

11.	GASKET (ENDLESS, MOULDED)	2	NEOPRENE
10.	TERMINAL	A.R.	CLIPON TYPE RAIL MOUNTED
09.	OVERLOAD RELAY	1	A.R
08.	CONTACTOR	2	A.R
07.	ACTUATOR RED-MUSHROOM HEAD	1	P.P
06.	ACTUATOR GREEN SHROUDED	1	P.P
05.	ACTUATOR BLUE SHROUDED	1	P.P
04.	WIRE BUSH	1	GLASSFEEL NYLONE
03.	TERMINAL BOX COVER	1	DIE CAST AL. ALLOY
02.	BODY COVER	1	DIE CAST AL. ALLOY
01.	BODY	1	DIE CAST AL. ALLOY
NO.	DESCRIPTION	QTY	MAT./RATING

CLIENT
CONSULTANT
P.O.No.

DRAWN *MLB/P*
CH'D *MLB/P*
APP'D *MLB/P*

01.09.16

DESCRIPTION:-
FLP. & WP. REVERSING
DOL STARTER UP TO 10HP



KAYSONS
TECHNO EQUIPMENTS PVT LTD

1802/7, G.I.D.C. ESTATE,
V.U.NAGAR 388121. (GUJARAT)

SHT.NO.
1 OF 1

REV.
0

DRG.NO.:-
G03

ISSUE DATE BY

MODIFICATION