



TECHNICAL DATA

ENCLOSURE :-
EX-d AS PER IS/IEC 60079-1:2007

PROTECTION :-
IP-66 AS PER IS 12063-1987 (IS/IEC 60529:2001)

AREA CLASSIFICATION :-
ZONE -1 & 2

TEMPERATURE CLASS :-
T6

GAS GROUPS :-
IIA & IIB

MATERIAL OF CONSTRUCTION :-
DIE CAST AL. ALLOY LM-6

HARDWARE :-
STEEL ZINC PLATED/STAINLESS STEEL

FINISH :-
LIGHT GREY POWDER COATED

EARTHING :-
1 NO. INSIDE & 2 NOS. OUTSIDE

CABLE ENTRY :-
3/4"ET - 3NOS.

10.	GASKET (ENDLESS, MOULDED)	2	NEOPRENE
09.	TERMINAL	A.R.	CLIPON TYPE
08.	SELECTOR SWITCH (AUTO-MANUAL)	1	A.R.
07.	AMMETER (GLASS WINDOW)	1	72mmX72mm
06.	ACTUATOR RED-MUSHROOM HEAD	1	P.P.
05.	ACTUATOR GREEN-SHROUDED	1	P.P.
04.	WIRE BUSH	1	GLASSFEEL NYLONE
03.	TERMINAL ENCLOSURE COVER	1	DIE CAST AL. ALLOY
02.	MAIN ENCLOSURE COVER	1	DIE CAST AL. ALLOY
01.	BODY	1	DIE CAST AL. ALLOY
NO.	DESCRIPTION	QTY	MAT./RATING

ISSUE	DATE	BY	MODIFICATION	CLIENT	CONSULTANT	P.O.No.	DRAWN	CH'D	APP'D	DESCRIPTION:-
							MSP	MSP	NPB	FLP WP. CONTROL STATION PUSH BUTTON.SWITCH & AMMETER.
										SHT.NO. 1 OF 1
										REV. 0
										DRG.NO.:- K08



KAYSONS
TECHNO EQUIPMENTS PVT LTD

1802/7, G.I.D.C. ESTATE,
V.U.NAGAR 388121. (GUJARAT)

01.09.16