



CIMFR CERT NO.:— CIMFR/TC/P/H681  
 SUPPLE. T.C. NO.:— CIMFR/TC/S/H139  
 TYPE/CAT NO.:— KRS-\*X\* SERIES

**SPECIFICATION**

TYPE OF PROTECTION :-  
 Ex'd' IIA, IIB & IIC AS PER IS/IEC 60079-1:2007

DEGREE OF INGRESS PROTECTION :-  
 IP-66 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :-  
 ZONE 1 & 2

GAS GROUPS :-  
 GROUP IIA, IIB & IIC.

CONSTRUCTION :-  
 BRASS NICKEL PLATED AS STANDARD  
 OPTIONAL S.S. OR M.S.

GASKET/O'RING :-  
 ENDLESS MOLDED NEOPRENE

ORDERING CODE :-  
 CAT. NO. FOLLOWED BY SIZE e.g. KRS-\*X\* M20x1.5 OR KRS-\*X\* 1/2"NPT

SIZE & CAT NO. :-

CAT.NO.	THD. SIZE (M) EXT/INT(MAX)	THD. SIZE (M) EXT/INT(MAX)	THD. SIZE (ET) EXT/INT(MAX)	THD. SIZE (ET) EXT/INT(MAX)	THD. SIZE (NPT) EXT/INT(MAX)	THD. SIZE (NPT) EXT/INT(MAX)	HEX	L
KRS-*X*	M12x1.5	M12x1.5	-	-	1/4"	1/4"	20	15
KRS-*X*	M16x1.5	M16x1.5	-	-	3/8"	3/8"	20	15
KRS-*X*	M20x1.5	M20x1.5	3/4"	3/4"	1/2"	1/2"	25	15
KRS-*X*	M25x1.5	M25x1.5	1"	1"	3/4"	3/4"	32	15
KRS-*X*	M32x1.5	M32x1.5	1-1/4"	1-1/4"	1"	1"	38	17.5
KRS-*X*	M40x1.5	M40x1.5	1-1/2"	1-1/2"	1-1/4"	1-1/4"	42	17.5
KRS-*X*	M50x1.5	M50x1.5	2"	2"	1-1/2"	1-1/2"	56	20
KRS-*X*	M63x1.5	M63x1.5	2-1/2"	2-1/2"	2"	2"	75	20
KRS-*X*	M75x1.5	M75x1.5	3"	3"	2-1/2"	2-1/2"	82	20
KRS-*X*	M100x1.5	M100x1.5	-	-	3"	3"	110	20

GASKET/O'RING NOT PROVIDED IN NPT THREADS

CLIENT		DRAWN	KBP	1.3.12	DESCRIPTION:- FLAMEPROOF & WEATHERPROOF REDUCER / SOCKET	
CONSULTANT		APP'D	HPB	1.3.12		
P.O.No.		CH'D	NPB	1.3.12		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE PROPERTY OF KAYSONS TECHNO EQUIPMENTS PVT. LTD. AND IS NOT TO BE COPIED OR MISUSED IN ANY WAY.		<b>KAYSONS</b> 1802/7, G.I.D.C. ESTATE, V.U.NAGAR 388121. (GUJARAT)		SHT.NO.	REV.	DRG.NO.:-
ISSUE	DATE	BY	MODIFICATION	1 OF 1	0	L05